

3D HDMI SWITCH

User Manual

HDMI 3x1 Switcher

(3D Full HD 1080P)

Bring High-Definition to your life!

INTRODUCTION

This is the final edition of high performance mini HDMI Amplifier Switcher.

This kind of HDMI mini switcher not only has the key-press-switching function, but also has the intelligent function.

This kind of HDMI Amplifier mini Switcher routes high definition video (in multiple resolutions up to 1080p) and digital audio from any one of the several sources to display units.

All inputs accommodate the connections of the high definition video sources simultaneously, compatible well for HD-DVD, SKY-STB, PS3, Xbox360 etc. The output sends the high definition audio/video signals to a high definition display.

Features

This Mini HDMI Amplifier Switcher has many features that enable it to perform in a superior manner. Among those features you will find:

- (1) Support 12-bit Deep Color, full 1080p(2) Support 3D
- (3) Multifunctional on switching : intelligent or mechanical
- (4) Supports with HDMI1.3b.
- (5) Supports Power Adapter 5V 1A
- (6) Supports IR Remote
- (7) High performance up to 2.5Gbps
- (8) Supports 25Meters HDMI Cable on both ends of the Switcher
- (9) Maintains high resolution video - beautiful, sharp HDTV resolutions up to 1080p, 2k, 1440p graphics and computer resolutions up to 1920 x 1200 are easily achieved

SPECIFICATIONS

Signal Inputs/Output	
Input Video Signal	0.5-1.0 volts p-p
Input DDC Signal	5 volts p-p (TTL)
Maximum Single Link Range	1920X1200, 1080P
Output Video	HDMI1.3b+HDCP1.0/1.1
Video format supported	
VGA	640x480, 800x600, 1024x768, 1920x1200
DTV/HDTV	480i/576i/480p/576p/720p/1080i/1080P
Digital Signal I/O	
HDMI Compliance	HDMI 1.3b

3D 1080P HDMI 3x1 SWITCH

Operating Frequency	50/60Hz
Frequency	
Vertical Frequency Range	60Hz
Video Amplifier Bandwidth	2.5Gpbs/250MHz
Resolutions (HDTV)	
Interlaced (50&60Hz)	480i, 576i, 1080i
Progressive (50&60Hz)	480p, 576p, 720p, 1080p
Mechanical	
Size (H-W-D)	80*58*17mm
Weight (Net)	145g
Warranty	
Limited Warranty	1 Year Parts and Labor
Environmental	
Operating Temperature	0°C to +70°C
Operating Humidity	10% to 85 % RH (no condensation)
Storage Temperature	-10°C to +80°C
Storage Humidity	5% to 90 % RH (no condensation)
Power Requirement	5V@1A
Accessories Adapter	
User Manual	English Version

Note: Specifications are subject to change without notice

Product Image

3D 1080P HDMI 3x1 SWITCH

